



2-Stroke

TC-W3 Ashless Formula

Features

- Low carbon-forming ashless formulation
- Additives for peak engine performance
- Suitable for pre-mix & injection system

Benefits

- Certified to highest NMMA performance standard TC-W3
- Provides deposit control
- Extends spark plug life
- Excellent rust and corrosion protection
- Easily pre-mixed at even the lowest winter temperatures

Cobra 2-STROKE Engine Oil is a premium lubricant for water-cooled outboard 2-stroke gasoline engines as well as liquid cooled engines typically used in ATVs, motorcycles, and snowmobiles. It is formulated using a high-quality base oil for low carbon-forming characteristics, ashless performance additives, and a solvent to improve mix-ability with gasoline.

Cobra 2-STROKE can be pre-mixed into gasoline or used in modern oil injection systems. The distinctive blue colour provides positive confirmation that the oil has been pre-mixed into the gasoline. The ashless formulation provides for clean pistons and cylinders while minimizing deposits that cause ring-sticking, port-plugging and pre-ignition, and it extends the life of the spark plugs. It also effectively prevents rust and corrosion, which is very important in the humid environment of outboard engines.

Cobra 2-STROKE is recommended for use in all water-cooled outboard 2-stroke gasoline engines, wherever the manufacturer recommends an NMMA- approved* lubricant. It is approved by the NMMA to its highest current performance standard, TC-W3. Tests by the engine manufacturers have shown this oil will DOUBLE the life of the powerhead, when compared to oils of the previous TC-WII category.

Cobra 2-STROKE is also recommended for use in some snowmobile engines, whether liquid- or air-cooled, wherever the manufacturer recommends an NMMA-approved or TC-W type lubricant.

Whether you're speeding across a lake on a personal watercraft or jumping sand dunes on your ATV, **Cobra 2-STROKE** will ensure your engine is running at top performance. Give some bite to your engine!

*NMMA: National Marine Manufacturers



2-Stroke

Typical performance results

COLOUR	BLUE
VISCOSITY (D-445) cSt @ 100°C	6.4
VISCOSITY INDEX (D-2270)	158
BROOKFIELD VISCOSITY cP @ -40°C	15,000
FLUIDITY/MISCIBILITY CLASSIFICATION	4
POUR POINT (°C) (D-97)	<-45
FLASH POINT (°C) (D-92)	114
SULPHATED ASH (% wt.) (D-874)	0
SOLVENT (%)	25.5
TOTAL BASE NUMBER (D-2896)	10.9

Check with sales representative or website for the latest product approvals.

Available sizes & part numbers

	473 ml. (1 US pint)	946 ml. (1 US qt)	3.78 L (1 US Gal)	205 L (54.2 US Gal)	Bulk
2-Stroke		FBB0005415			



Cobra Quality & Value

www.cobralubricants.com